

ACCESS HOLDINGS INTERNATIONAL

+61 2 9749 5686

access@ahiholdings.com  
www.ahiholdings.com

# Up-Lift®

Personnel Lift



## UE Series

### Central Mast

- Unique stainless steel cage
- Concentric mast design
- High quality spiral cable
- Emergency down valve
- Back-up battery system
- Trailer loading device
- Descend alarm
- Convenient platform controls
- Standard doorway access
- UE32/40/48 tilt back support
- Safe and reliable, complies with relevant standards
- Choice of 5 standard platform heights from 6.1m to 14.5m

**UE20 6.1 metres**

**UE25 7.6 metres**

**UE32 9.7 metres**

**UE40 12.3 metres**

**UE48 14.5 metres**

### Applications:

The central mast design delivers high stability, complete safety and enhanced comfort level to the operator.

Use of high quality and highly durable aircraft standard aluminium greatly reduces weight and strengthens the structure of the machine. with special attention gives to practical features and safety standards, the UE series man lifts enjoy greater stability and safety and is unique in many ways.

UE personnel lifts are available in both AC and DC versions

### Options:

Laser position locator

Dual power source

Fibreglass cage



### Technical Specifications

Model	UE20	UE25	UE32	UE40	UE48
Max Platform Height (m)	6.1	7.6	9.7	12.3	14.5
Max Working Height (m)	8.1	9.6	11.7	14.3	16.5
Rated Load (kg)	159	159	136	136	110
Stored Dimensions (m)	1.29x0.74x1.82	1.29x0.74x1.98	1.31x0.74x2.53	1.31x0.74x2.93	1.31x0.74x3.35
Tilted Dimensions (m)	N/A	N/A	2.53x0.74x1.83	3.07x0.74x1.97	3.35x0.74x1.98
Platform Dimensions (m)	0.68x0.66x1.32	0.68x0.66x1.32	0.68x0.66x1.32	0.68x0.66x1.32	0.68x0.66x1.32
Outrigger Foot-Print (m)	1.47x1.55	1.47x1.55	2.10x2.20	2.40x2.50	2.90x3.03
Wall Access-Distance (m)	0.10	0.10	0.37	0.53	0.72
Voltage (V) AC/DC	230/12	230/12	230/12	230/12	230/12
Total Weight (kg) AC/DC	320/362	350/392	430/472	460/502	520/562
Power Rating (kW) AC/DC	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6